

ARMOR LATEX

Styrene butadiene copolymer latex Admixture

Product Description:

ARMORLATEX is a styrene butadiene copolymer latex admixture that is designed as an integral adhesive for cement, bond coats, mortar and concrete to improve bond strength, chemical resistance and waterproofing properties

Typical Applications:

ARMORLATEX can be used in the following areas:

- Concrete repairs and Patching
- Floor screed and toppings
- External rendering
- Waterproofing and tanking
- Corrosion protection of steel

Advantages And Benefits:

- Improves Flexural and tensile strength of concrete and mortar.
- Improves the weather resistance of concrete and mortar, by reducing the impact of chloride and other agents
- It is simple and easy to use and helps to achieve low water cement ratio
- Improve corrosion protection
- Helps to improve the waterproofing properties of concrete and mortar
- Proven Performance and versatility of Usage

Product Application:

- Surface should be clean, sound and free oil
- Dams, culverts, canals and spillways
- Swimming pools
- Car park Static bunded areas surrounding liquid retaining tanks
- Basement and underground car park
- Tunnels and Subways
- Abutments and Retaining wall
- Roof decks and Podium areas

Technical Data:

Chemical type	Acrylic cement modifier
Appearance	Milky white liquid
Solubility	Disposable in water
Specific gravity	1.0 to 1.2
Shelf life	12 months
Curvy time	28days



ARMORSIL MANUFACTURING INCORPORATION

Sede legale: VIA Montello 48,INT #3 Pordenone, Italy. 33170. Tel: + 30256365-16

www.armorsil.com, info@armorsil.com , sales@armorsil.com

Limited Warranty

All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use away.

Armorsil Manufacturing supplies products that comply with the properties shown on the current datasheets. In the unlikely event that products supplied are proved not to comply with these properties, then we will replace the non-compliant product or refund the purchase price. Armorsil Manufacturing does not warrant or guarantee the installation of the products as it does not have control over the installation or end use of the products. Any suspected defects must be reported to Armorsil Manufacturing in writing within seven working days of being detected.

Armorsil Manufacturing. Makes no warranty as to merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties express or implied. Neither seller nor Armorsil Manufacturing shall be liable to the buyer or any third person for any injury, loss or damages of any sort including remote or consequential damages, down time, or delay directly or indirectly resulting from use of or inability to use the product. . The information contained in the latest data sheet supersedes all previously published editions. Visits to site by Armorsil personnel do not constitute supervisory responsibility. Armorsil reserves the right to alter the information contained in this datasheet without prior notice