

# Plast Proof 200

## Anti crack, Water repellent admixture for Plaster

### Product Description:

**Plast proof 200** is an anti crack integral water repellent powder waterproofing admixture for plaster. Plast proof 200 helps to repel water absorption from wind rain and other sources from wall plasters and reduce the formation of efflorescence.

### Advantages:

- It protects structure from wind rain and helps to protect your wall plaster from moisture
- Penetration and water damage for a long time.
- Increases resistance to weathering, such as wetting and drying and freeze-thaw cycle.
- Reduced primary and secondary efflorescence on structures
- Solvent free and low VOC

### Uses:

- Plast proof 200 is particularly suited to mortar and plaster requiring requiring waterproofing against
- Wind rain, water damage and efflorescence.
- The anti crack property of Plast proof 200 also helps to reduce incidence of crack due to bad
- Workmanship and hot weather

### Packaging:

20kg bags

### Shell Life:

12 months

### Yield:

Varies with water content  
Installation Guideline

### Armorsil Manufacturing:

Armorsil provides detailed method statements on all its products for use in various applications. Below is an information summary for guidance.

### Consumption:

The recommended dosage for Plast proof 200 is 0.5 kg per bag of 50kg cement. Note that optimum dosage to meet specific requirements should always be determined by trial mixes using admixture on site

## Material Properties

---

Appearance: Light grey

## Health And Safety:

---

Like all material that contains Portland cement, this material must be handled professionally as it can cause irritation and burns.



**ARMORSIL MANUFACTURING INCORPORATION**

Sede legale: VIA Montello 48, INT #3 Pordenone, Italy. 33170. Tel: + 30256365-16

[www.armorsil.com](http://www.armorsil.com), [info@armorsil.com](mailto:info@armorsil.com), [sales@armorsil.com](mailto:sales@armorsil.com)

### Limited Warranty

All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied

materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use away.

Armorsil Manufacturing supplies products that comply with the properties shown on the current datasheets. In the unlikely event that products supplied are proved not to comply with these properties, then we will replace the non-compliant product or refund the purchase price. Armorsil Manufacturing does not warrant or guarantee the installation of the products as it does not have control over the installation or end use of the products. Any suspected defects must be reported to Armorsil Manufacturing in writing within seven working days of being detected.

Armorsil Manufacturing. Makes no warranty as to merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties express or implied. Neither seller nor Armorsil Manufacturing shall be liable to the buyer or any third person for any injury, loss or damages of any sort including remote or consequential damages, down time, or delay directly or indirectly resulting from use of or inability to use the product. . The information contained in the latest data sheet supersedes all previously published editions. Visits to site by Armorsil personnel do not constitute supervisory responsibility. Armorsil reserves the right to alter the information contained in this datasheet without prior notice.

