

ARMORFIX 115

Slip Resistant Fast Set Heavy Duty Tile Adhesive

Product Description:

ARMORFIX -115 is a heavy duty, Slip resistant and water repellent cement based ceramic tile adhesive. It is suitable for thin and thick bed applications, internal and external applications. ARMORFIX -115 enables the same day fixing and grouting.

It is suitable for the fixing of ceramic tiles on floor and wall of concrete, concrete block and cement render. It can also be used for the fixing of glass mosaic, stone marble, Pre-cast concrete facings, terrazzo and brick slips. When used, Armor primer 106 can also be used for fixing tiles on gypsum plaster, plaster board, chipboard and wood. It is suitable for use in Swimming pools as well.

Advantages:

-) High adhesive tensile strength
-) Because of the impressive slip resistant ability it can be used for vertical and horizontal placement of large tiles
-) Conforms to C2 F S2 to BS EN 12004
-) Highly flexible and rapid setting
-) Non sag properties with high initial adhesiveness
-) Greater workability due to high pot life
-) Impressive waterproof properties

Uses:

For the installation of floor and wall ceramic tiles, glass mosaic, stone marble, terrazzo, and brick slips, plaster boards, gypsum plaster, plasterboard and wood.

Surface Preparation:

The substrate must be fully cured and well prepared, it must be sound, clean, structurally stable, free from dirt, loose particles, efflorescence, chemicals and other contaminants, in order to ensure proper bonding.

Application Instruction:

Pour ARMORFIX -115 into a clean plastic or metal bucket containing clean water, pour adequate quantity of ARMORFIX-115 that can be used within the pot life of 4 hours. .25kg of ARMORFIX -115 requires approximately 4 litres of water. Stir with a mixing device or by hand. Let the mixture rest for 10-15 minutes and restart briefly before application. No more water should be added after mixing.

Application and Installation:

-) **Spread** ARMORFIX -115 tile adhesive mortar evenly over 1m² areas at a time using a notched trowel. **Fix tiles immediately within the open time of 20 minutes. Please be sure that all areas are covered with ARMORFIX -115 tile adhesive.**

Coverage:

For thin solid bed application (3mm thickness) 4-5kg of ARMORFIX -115 will cover approximately 1m²

Packaging:

Available in 20kg bags and buckets

Cleaning And Health:

Remove the excess mortar on tools with copious amount of water; if already dry you can remove through mechanical means. Also prolonged contact with skin may occur as it is the case with all cementitious based material, therefore safety gloves and glasses should be used when working.

Shelf Life:

Store in a cold dry place. With proper storage material can be stored and used within 12 months.

Technical Data:

Test Property	Result	Test Method
Conforms to C2 F S2 to BS EN 12004		EN12004
Minimum tensile Adhesion strength		
28 days dry	≥1mpA	
28 days wet	≥1mpA	
24 hours dry slip resistance	≤0.5mm	
Transverse deformation	2.5mm and ≤5mm	
Working Properties		
Open time	40 minutes	
Pot life	2 hours	
Time to traffic	24 hours	

Limited Warranty

All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use away.

Armorsil Manufacturing supplies products that comply with the properties shown on the current datasheets. In the unlikely event that products supplied are proved not to comply with these properties, then we will replace the non-compliant product or refund the purchase price. Armorsil Manufacturing does not warrant or guarantee the installation of the products as it does not have control over the installation or end use of the products. Any suspected defects must be reported to Armorsil Manufacturing in writing within seven working days of being detected.

Armorsil Manufacturing. Makes no warranty as to merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties express or implied. Neither seller nor Armorsil Manufacturing shall be liable to the buyer or any third person for any injury, loss or damages of any sort including remote or consequential damages, down time, or delay directly or indirectly resulting from use of or inability to use the product. . The information contained in the latest data sheet supersedes all previously published editions. Visits to site by Armorsil personnel do not constitute supervisory responsibility. Armorsil reserves the right to alter the information contained in this datasheet without prior notice



ARMORSIL MANUFACTURING INCORPORATION

) 4636 Chestnut Street, Philadelphia, Pennsylvania 19139 . Tel : +1 209 813 246 +1 415 670 9521
) www.armorsil.com, info@armorsil.com, sales@armorsil.com

PROVIDING ARMOR FOR BUILDING

www.armorsil.com